

PRO400 BOTTOM STRAIGHT 180°



PRODUCT DESCRIPTION

Pro inspection chambers are made of polypropylene (PP) and comply with standard **EN 13598-2**.

The installation depth of the Pro400 chambers can vary between 1m and up to 6m. They are also, in the long term, resistant to the presence of groundwater up to 5m above the bottom of the chamber.

This inspection chamber is constructed using a **bottom**, a **smooth riser pipe**, a **telescope** and a **concrete ring with cover**. The interconnections should be provided with **rubber seals**.

This Pro Ø400 has a straight flow profile and connections can be made with smooth PVC pipes. Swivel joints, up to 15°, are also included in the range.

When installing this chamber the following points must be followed:

- The soil around the chamber must be well compacted.
- Clean soil free of stones or other sharp objects must be used.

Material: PP


Color: Redbrown (RAL 8023)

Connection 1: Socket

Connection 2: Socket

O13

MEASUREMENT DRAWING



Article no.	EAN	Description	Diameter	Height (H)	Connections	N° of units
3496100471	5905485404761	PP PRO IC 400 FLOW PROFILE 180° 2x160	400 mm	383 mm	160 mm	1
3496100462	5905485443005	PP PRO IC 400 FLOW PROFILE 180° 2x200	400 mm	423 mm	200 mm	1
3496100589	5905485443036	PP PRO IC 400 FLOW PROFILE 180° 2x250	400 mm	635 mm	250 mm	1
3496100617	5905485443050	PP PRO IC 400 FLOW PROFILE 180° 2x315	400 mm	635 mm	315 mm	1
3496100628	5905485443067	PP PRO IC 400 FLOW PROFILE 180° 2x400	400 mm	635 mm	400 mm	1