

## PRO400 BOTTOM DOUBLE Y



### PRODUCT DESCRIPTION

Pro inspection chambers are made of polypropylene (PP) and comply with standard EN 13598-2.

The installation depth of the Pro400 chambers can vary between 1m and up to 6m. They are also, in the long term, resistant to the presence of groundwater up to 5m above the bottom of the chamber.

This inspection chamber is constructed using a **bottom**, a **smooth riser pipe**, a **telescope** and a **concrete ring with cover**. The interconnections should be provided with **rubber seals**.

This Pro Ø400 has a double T flow profile and connections can be made with smooth PVC pipes. Swivel joints, up to 15°, are also included in the range.

When installing this chamber the following points must be followed:

- The soil around the chamber must be well compacted.
- Clean soil free of stones or other sharp objects must be used.

Material: PP

Color: Redbrown (RAL 8023)

Connection 1: Socket

Connection 2: Socket

Connection 3: Socket

Connection 4: Spigot

O13

Article no.	EAN	Description	Diameter	Height (H)	Connections	N° of units
3496100524	5905485443210	PP PRO IC 400 FLOW PR. MULTI 45° 4x110	400 mm	348 mm	110 mm	1
3496100525	5905485404914	PP PRO IC 400 FLOW PR. MULTI 45° 4x160	400 mm	398 mm	160 mm	1
3496100526	5905485443326	PP PRO IC 400 FLOW PR. MULTI 45° 4x200	400 mm	438 mm	200 mm	1

**BUILDING SOLUTIONS**

buildings@pipelife.be

**INFRA SOLUTIONS**

infra@pipelife.be