

PRO630 BOTTOM DOUBLE Y



PRODUCT DESCRIPTION

Pro inspection chambers are made of polypropylene (PP) and comply with standard EN 13598-2.

The Pro Ø630 is fitted with a double bottom which increases its strength and, when groundwater is present, eliminates its impact on the soil. The shape of the bottom and the ridges on the wall also provide excellent resistance to soil or groundwater pressure. The installation depth of these chambers can vary between 1m and up to 6m. They are also, in the long term, resistant to the presence of groundwater up to 5m above the bottom of the chamber.

This inspection chamber is constructed using a **bottom**, a **corrugated riser pipe**, a **telescope** and a **concrete ring with cover**. The interconnections should be provided with **rubber seals**.

This Pro Ø630 has a double T flow profile and connections can be made in either smooth or ribbed Pragma pipe. If you want to make a connection for a ribbed Pragma pipe, an adapter must be used. Swivel joints, up to 15°, are also included in the range.

When installing this chamber the following points must be followed: – The soil around the chamber must be well compacted. – Clean soil free of stones or other sharp objects must be used.

Material: PP

Color: Redbrown (RAL 8023)

Connection 1: Socket

Connection 2: Socket

Connection 3: Socket

Connection 4: Socket

O13

Article no.	EAN	Description	Diameter	Height (H)	Connections	Angle	N° of units
3496100694	5905485443791	PP PRO IC 630 FLOW PR. MULTI 45° 4x250	630 mm	613 mm	250 mm	45 °	1
3496102428	5905485463621	PP PRO IC 630 FLOW PR. MULTI 90° 4x250	630 mm	613 mm	250 mm	90 °	1
3496102430	5905485463645	PP PRO IC 630 FLOW PR. MULTI 90° 4x315	630 mm	613 mm	315 mm	90 °	1