

PRO800 BOTTOM STRAIGHT 180°



PRODUCT DESCRIPTION

Pro inspection chambers are made of polypropylene (PP) and comply with standard **EN 13598-2**.

The Pro Ø800 is fitted with a double bottom which increases its strength and, when groundwater is present, eliminates its impact on the soil. The shape of the bottom and the ridges on the wall also provide excellent resistance to soil or groundwater pressure. The installation depth of these chambers can vary between 1m and up to 6m. They are also, in the long term, resistant to the presence of groundwater up to 5m above the bottom of the chamber. It should be noted that in soils with high level of groundwater reaching above 1m from the bottom of the base, it is recommended to use appropriate means of protection for the chamber. (e.g. concreting)

This inspection chamber is constructed using a **bottom, a riser ring, a cone and a concrete ring with cover**. The interconnections should be provided with **rubber seals**.

This Pro Ø800 has a straight flow profile and connections can be made in either smooth or ribbed Pragma pipe. If you want to make a connection for a ribbed Pragma pipe, an adapter must be used.

Swivel joints, up to 15°, are also included in the range.

When installing this chamber the following points must be followed:

- The soil around the chamber must be well compacted.
- Clean soil free of stones or other sharp objects must be used.

Material: PP

Color: Redbrown (RAL 8023)

Connection 1: Socket

Connection 2: Socket

O13

Article no.	EAN	Description	Diameter	Height (H)	Connections	N° of units
3496101292	5905485446877	PP PRO IC 800 FLOW PROFILE 180° 2x250	800 mm	545 mm	250 mm	1
3496101293	5905485446884	PP PRO IC 800 FLOW PROFILE 180° 2x315	800 mm	690 mm	315 mm	1
3496101294	5905485446891	PP PRO IC 800 FLOW PROFILE 180° 2x400	800 mm	690 mm	400 mm	1