

MASTER3 PLUS BRANCH BLACK



PRODUCT DESCRIPTION

With Master3Plus, you can choose between single or double socketed fittings.

The socketed fittings guarantee fast, failsafe and flexible sealing thanks to:

- Highly reliable EPDM sealing ring
- Reinforcing ribs positioned at a 60° angle, help you to orientate the fitting correctly
- Insertion-depth marking helps you to instantly tell if the products have been connected correctly.

Thanks to the assortment of 200+ articles, a suitable soil and waste system can be designed for any installation, no matter how complex.

Article no.	Angle	Conn.1	Conn.2	Conn.3	Ø	Ø2	Ø3
3496102866	45 °	Socket	Socket	Spigot	32 mm	32 mm	32 mm
3496103123	45 °	Socket	Socket	Spigot	40 mm	40 mm	32 mm
3496102637	45 °	Socket	Socket	Spigot	40 mm	40 mm	40 mm
3496103125	45 °	Socket	Socket	Spigot	50 mm	50 mm	32 mm
3496103127	45 °	Socket	Socket	Spigot	50 mm	50 mm	40 mm
3496102647	45 °	Socket	Socket	Spigot	50 mm	50 mm	50 mm
3496102651	45 °	Socket	Socket	Spigot	75 mm	75 mm	50 mm
3496102656	45 °	Socket	Socket	Spigot	75 mm	75 mm	75 mm
3496102661	45 °	Socket	Socket	Spigot	90 mm	90 mm	50 mm
3496102665	45 °	Socket	Socket	Spigot	90 mm	90 mm	75 mm
3496102669	45 °	Socket	Socket	Spigot	90 mm	90 mm	90 mm
3496102512	45 °	Socket	Socket	Spigot	110 mm	110 mm	50 mm
3496102679	45 °	Socket	Socket	Spigot	110 mm	110 mm	75 mm
3496102684	45 °	Socket	Socket	Spigot	110 mm	110 mm	90 mm
3496102518	45 °	Socket	Socket	Spigot	110 mm	110 mm	110 mm
3496102692	45 °	Socket	Socket	Spigot	125 mm	125 mm	110 mm
3496102698	45 °	Socket	Socket	Spigot	125 mm	125 mm	125 mm
3496102704	45 °	Socket	Socket	Spigot	160 mm	160 mm	110 mm
3496102756	45 °	Socket	Socket	Spigot	160 mm	160 mm	125 mm
3496102709	45 °	Socket	Socket	Spigot	160 mm	160 mm	160 mm