

# MASTER3 PLUS BRANCH BLACK



## PRODUCT DESCRIPTION

With Master3Plus, you can choose between single or double socketed fittings.

The socketed fittings guarantee fast, failsafe and flexible sealing thanks to:

- Highly reliable EPDM sealing ring
- Reinforcing ribs positioned at a 60° angle, help you to orientate the fitting correctly
- Insertion-depth marking helps you to instantly tell if the products have been connected correctly.

Thanks to the assortment of 200+ articles, a suitable soil and waste system can be designed for any installation, no matter how complex.

Article no.	Angle	Conn.1	Conn.2	Conn.3	Ø	Ø2	Ø3	Info
3496102867	87,5 °	Socket	Socket	Spigot	32 mm	32 mm	32 mm	
3496103124	87,5 °	Socket	Socket	Spigot	40 mm	40 mm	32 mm	
3496102640	87,5 °	Socket	Socket	Spigot	40 mm	40 mm	40 mm	
3496103126	87,5 °	Socket	Socket	Spigot	50 mm	50 mm	32 mm	
3496103128	87,5 °	Socket	Socket	Spigot	50 mm	50 mm	40 mm	
3496102509	87,5 °	Socket	Socket	Spigot	50 mm	50 mm	50 mm	
3496102654	87,5 °	Socket	Socket	Spigot	75 mm	75 mm	50 mm	
3496102659	87,5 °	Socket	Socket	Spigot	75 mm	75 mm	75 mm	
3496102663	87,5 °	Socket	Socket	Spigot	90 mm	90 mm	50 mm	
3496102667	87,5 °	Socket	Socket	Spigot	90 mm	90 mm	75 mm	
3496102672	87,5 °	Socket	Socket	Spigot	90 mm	90 mm	90 mm	Flow-T
3496102515	87,5 °	Socket	Socket	Spigot	110 mm	110 mm	50 mm	
3496102682	87,5 °	Socket	Socket	Spigot	110 mm	110 mm	75 mm	
3496102686	87,5 °	Socket	Socket	Spigot	110 mm	110 mm	90 mm	Flow-T
3496102689	87,5 °	Socket	Socket	Spigot	110 mm	110 mm	110 mm	Flow-T
3496102695	87,5 °	Socket	Socket	Spigot	125 mm	125 mm	110 mm	
3496102701	87,5 °	Socket	Socket	Spigot	125 mm	125 mm	125 mm	
3496102706	87,5 °	Socket	Socket	Spigot	160 mm	160 mm	110 mm	
3496102711	87,5 °	Socket	Socket	Spigot	160 mm	160 mm	160 mm	