

MASTER3PLUS BRANCH BLACK ALL SOCKETS



PRODUCT DESCRIPTION

With Master3Plus, you can choose between single or double socketed fittings.

The socketed fittings guarantee fast, failsafe and flexible sealing thanks to:

- Highly reliable EPDM sealing ring
- Reinforcing ribs positioned at a 60° angle, help you to orientate the fitting correctly
- Insertion-depth marking helps you to instantly tell if the products have been connected correctly.

Thanks to the assortment of 200+ articles, a suitable soil and waste system can be designed for any installation, no matter how complex.

Article no.	Angle	Conn.1	Conn.2	Conn.3	Ø	Ø2	Ø3	Info
3496102641	87,5 °	Socket	Socket	Socket	40 mm	40 mm	40 mm	
3496102510	87,5 °	Socket	Socket	Socket	50 mm	50 mm	50 mm	
3496102655	87,5 °	Socket	Socket	Socket	75 mm	75 mm	50 mm	
3496102757	87,5 °	Socket	Socket	Socket	75 mm	75 mm	75 mm	
3496102674	87,5 °	Socket	Socket	Socket	90 mm	90 mm	90 mm	
3496102516	87,5 °	Socket	Socket	Socket	110 mm	110 mm	50 mm	
3496102690	87,5 °	Socket	Socket	Socket	110 mm	110 mm	110 mm	Flow-T
3496102696	87,5 °	Socket	Socket	Socket	125 mm	125 mm	110 mm	
3496102702	87,5 °	Socket	Socket	Socket	125 mm	125 mm	125 mm	