

PRO630 BOTTOM BEND 90°



PRODUCT DESCRIPTION

Pro inspection chambers are made of polypropylene (PP) and comply with standard **EN 13598-2**.

The Pro Ø630 is fitted with a double bottom which increases its strength and, when groundwater is present, eliminates its impact on the soil. The shape of the bottom and the ridges on the wall also provide excellent resistance to soil or groundwater pressure. The installation depth of these chambers can vary between 1m and up to 6m. They are also, in the long term, resistant to the presence of groundwater up to 5m above the bottom of the chamber.

This inspection chamber is constructed using a **bottom, a corrugated riser pipe, a telescope and a concrete ring with cover**. The interconnections should be provided with **rubber seals**.

This Pro Ø630 has a bended flow profile and connections can be made in either smooth or ribbed Pragma pipe. If you want to make a connection for a ribbed Pragma pipe, an adapter must be used. Swivel joints, up to 15°, are also included in the range.

When installing this chamber the following points must be followed: – The soil around the chamber must be well compacted. – Clean soil free of stones or other sharp objects must be used.

Material: PP

Color: Redbrown (RAL 8023)

Connection 1: Socket

Connection 2: Socket

O13

Article no.	EAN	Description	Diameter	Height (H)	Connections	Angle	N° of units
3496102425	5905485463591	PP PRO IC 630 FLOW PR. BEND 90° 2x200	630 mm	613 mm	200 mm	90 °	1
3496100638	5905485443845	PP PRO IC 630 FLOW PR. BEND 90° 2x250	630 mm	613 mm	250 mm	90 °	1
3496100654	5905485443869	PP PRO IC 630 FLOW PR. BEND 90° 2x315	630 mm	613 mm	315 mm	90 °	1