

PVC FLEXIBLE INSTALLATION PIPES TAM 750N

Standard EN 61386-22



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 750N

Marking: 3341

Colour: beige, RAL 1015

Temperature range: -25 °C to +60 °C

Area of application: Universal flexible pipe, which is also suitable for use at lower temperatures. Can be installed in concrete, stone floors, walls and ceilings, on and under wood and plaster.

Article number	Old article number	Diameter D	Inner-diameter	Lenght	Ring stiffness	Flexibility	Pipe surface	Quantity on pallet pcs
70000744	70005352	16 mm	10,45 mm	50 m	750N	coiled	corrugated	30
70012160	70005353	20 mm	13,8 mm	50 m	750N	coiled	corrugated	20
70000748		25 mm	18,15 mm	25 m	750N	coiled	corrugated	24
70000751		32 mm	24,5 mm	25 m	750N	coiled	corrugated	15
70012161		40 mm	31,4 mm	25 m	750N	coiled	corrugated	14
70012162		50 mm	39,7 mm	25 m	750N	coiled	corrugated	8

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)