

PVC LOW FRICTION RIGID INSTALLATION PIPES 750N 2,5M

Standard EN 61386-21



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 750N

Marking: 3441

Colour: beige, RAL 1015

Temperature range: -25 °C to +60 °C

Length: 2,5 m, without socket

Field of application: Pipes with increased mechanical strength, suitable for installing at lower temperatures. Can be spring-loaded and installed in concrete.

Article number	Diameter D	Length	Ring stiffness	Flexibility	Inner layer	Quantity on pallet pcs	Quantity in package pcs
70005376	16 mm	2,5 m	750N	rigid	Silicone inner layer	1428	51
70005377	20 mm	2,5 m	750N	rigid	Silicone inner layer	888	37
70005378	25 mm	2,5 m	750N	rigid	Silicone inner layer	1008	24
70005379	32 mm	2,5 m	750N	rigid	Silicone inner layer	665	19
70005380	40 mm	2,5 m	750N	rigid	Silicone inner layer	490	10
70005381	50 mm	2,5 m	750N	rigid	Silicone inner layer	245	7

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)