

PVC PLIABLE INSTALLATION PIPES WITH WIRE EXL-W 320N

Standard EN 61386-22



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 320N

Marking: 22211

Colour: gray

Temperature range: -5 °C to +60 °C

The retraction wire simplifies and speeds up installation work.

Field of application: Suitable as an insulation and installation pipe both for on open surface and under the plaster. Not suitable for installation in concrete.

| Article number | Old article number | Diameter D | Inner-diameter | Lenght | Ring stiffness | Flexibility | with draw wire | Pipe surface | Quantity on pallet pcs |
|----------------|--------------------|------------|----------------|--------|----------------|-------------|----------------|--------------|------------------------|
| 1396500016 | 1196020700 | 16 mm | 11 mm | 50 m | 320N | coiled | yes | corrugated | 40 |
| 1396500020 | 1196043800 | 20 mm | 14 mm | 50 m | 320N | coiled | yes | corrugated | 28 |
| 1396500025 | 1196074100 | 25 mm | 18,6 mm | 50 m | 320N | coiled | yes | corrugated | 20 |
| 1396500032 | 1196114600 | 32 mm | 24,4 mm | 25 m | 320N | coiled | yes | corrugated | 24 |
| 1396500040 | 1196143700 | 40 mm | 31,7 mm | 25 m | 320N | coiled | yes | corrugated | 20 |
| 1396500050 | 1196191500 | 50 mm | 39,9 mm | 25 m | 320N | coiled | yes | corrugated | 10 |

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
 Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)