

PVC PLIABLE INSTALLATION PIPES WITH WIRE EXL-W 320N

Standard EN 61386-22



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 320N

Marking: 22211

Colour: gray

Temperature range: -5 °C to +60 °C

The retraction wire simplifies and speeds up installation work.

Field of application: Suitable as an insulation and installation pipe both for on open surface and under the plaster. Not suitable for installation in concrete.

Article number	Old article number	Diameter D	Inner-diameter	Lenght	Ring stiffness	Flexibility	with draw wire	Pipe surface	Quantity on pallet pcs
1396500016	1196020700	16 mm	11 mm	50 m	320N	coiled	yes	corrugated	40
1396500020	1196043800	20 mm	14 mm	50 m	320N	coiled	yes	corrugated	28
1396500025	1196074100	25 mm	18,6 mm	50 m	320N	coiled	yes	corrugated	20
1396500032	1196114600	32 mm	24,4 mm	25 m	320N	coiled	yes	corrugated	24
1396500040	1196143700	40 mm	31,7 mm	25 m	320N	coiled	yes	corrugated	20
1396500050	1196191500	50 mm	39,9 mm	25 m	320N	coiled	yes	corrugated	10

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
 Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)