

PVC UV RESISTANT PLIABLE INSTALLATION PIPES WITH WIRE EXM-W-UV 750N

Standard EN 61386-22



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 750N

Marking: 3341

Colour: black, RAL 9005

Temperature range: -25 °C to +60 °C

The retraction wire simplifies and speeds up installation work.

Field of application: Universal flexible pipe, which is also suitable for use in lower temperatures. Can be installed on concrete, stone floors, walls and ceilings, on and under wood and plaster.

Article number	Old article number	Diameter D	Inner-diameter	Lenght	Ring stiffness	Flexibility	with draw wire	Pipe surface	Quantity on pallet pcs
1396500116	1196020900	16 mm	10,8 mm	50 m	750N	coiled	yes	corrugated	40
1396500120	1196044000	20 mm	13,8 mm	50 m	750N	coiled	yes	corrugated	28
1396500125	1196074300	25 mm	18,3 mm	50 m	750N	coiled	yes	corrugated	20
1396500132	1196114800	32 mm	24,1 mm	25 m	750N	coiled	yes	corrugated	24
1396500140	1196143800	40 mm	31,4 mm	25 m	750N	coiled	yes	corrugated	20
1396500150	1196191200	50 mm	39,7 mm	25 m	750N	coiled	yes	corrugated	10

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
 Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)