

## PVC RIGID INSTALLATION PIPES 320N 3M

Standard EN 61386-21



### LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 320N

Marking: 22211

Colour: gray, RAL 7035

Temperature range: -5 °C to +60 °C

Length: 3,0 m, with socket

Field of application: Insulation and installation pipe both for open surface and under the plaster. Not suitable for installation in concrete.

| Article number | Old article number | Diameter D | Inner-diameter | Length | Ring stiffness | Flexibility | Quantity on pallet pcs | Quantity in package pcs |
|----------------|--------------------|------------|----------------|--------|----------------|-------------|------------------------|-------------------------|
| 1396325316     | 70012195           | 16 mm      | 14 mm          | 3 m    | 320N           | rigid       | 1295                   | 37                      |
| 1396325320     | 70012196           | 20 mm      | 17,8 mm        | 3 m    | 320N           | rigid       | 925                    | 37                      |
| 1396325325     | 70012197           | 25 mm      | 22,6 mm        | 3 m    | 320N           | rigid       | 570                    | 19                      |
| 1396325332     | 70012198           | 32 mm      | 29,4 mm        | 3 m    | 320N           | rigid       | 342                    | 19                      |
| 1396325340     | 70012199           | 40 mm      | 37 mm          | 3 m    | 320N           | rigid       | 210                    | 7                       |
| 1396325350     | 70012200           | 50 mm      | 46,4 mm        | 3 m    | 320N           | rigid       | 126                    | 7                       |

#### Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa  
Telephone: +372 605 5160

e-mail: [pipelife@pipelife.ee](mailto:pipelife@pipelife.ee) · [Privacy policy](#) · [Cookie information](#)