

PVC RIGID INSTALLATION PIPES 320N 3M

Standard EN 61386-21



LONG MARKETING TEXT

Material: PVC-U

Stiffness class: 320N

Marking: 22211

Colour: gray, RAL 7035

Temperature range: -5 °C to +60 °C

Length: 3,0 m, with socket

Field of application: Insulation and installation pipe both for open surface and under the plaster. Not suitable for installation in concrete.

Article number	Old article number	Diameter D	Inner-diameter	Length	Ring stiffness	Flexibility	Quantity on pallet pcs	Quantity in package pcs
1396325316	70012195	16 mm	14 mm	3 m	320N	rigid	1295	37
1396325320	70012196	20 mm	17,8 mm	3 m	320N	rigid	925	37
1396325325	70012197	25 mm	22,6 mm	3 m	320N	rigid	570	19
1396325332	70012198	32 mm	29,4 mm	3 m	320N	rigid	342	19
1396325340	70012199	40 mm	37 mm	3 m	320N	rigid	210	7
1396325350	70012200	50 mm	46,4 mm	3 m	320N	rigid	126	7

Pipelife Estonia

Põrguvälja tee 4, Lehmja, Rae vald · 75306 Harjumaa
Telephone: +372 605 5160

e-mail: pipelife@pipelife.ee · [Privacy policy](#) · [Cookie information](#)