



Product Inflex

Producer Pipelife Sverige AB, Ljung, Sweden (DIM 16 and 20mm)
Pipelife Deutschland GmbH Germany (25, 32, 40 and 50mm)

Usage Indoor electro installation

Information INFLEX, flexible corrugated installation pipe in PP.

Technical data	Dimensions:	OD 16mm	ID 11,4mm	
		OD 20mm	ID 13,9mm	
		OD 25mm	ID 18,5mm	
		OD 32mm	ID 25,1mm	
		OD 40mm	ID 32,0mm	
		OD 50mm	ID 40,2mm	
		Halogen free:	Yes	
		Flame retardant:	Yes	
		Bending strength:	Flexible	
		With sleeve:	No	
		Compression strength:	Medium (3)	
		Impact strength:	Medium (3)	
		Flush mounted:	Yes	
	Surface mounted :	Yes		
	Suitable for installation in wood:	Yes		
	Suitable for hollow installation:	Yes		
	Suitable for concrete installation:	Yes		
	Machine and system installation:	No		
	Suitable for subsurface installation:	Yes		
	Outdoor installation:	No		
	Underground installation:	No		
	Operating temperature:	-25degC to 90degC		
	Color of pipe:	Grey		

Marking "Pipelife PP [DIM] 33 422 267—10 [SEO] alt. [DEB]"

Quality Pipelife quality system according to EN ISO 9001:2000

Approvals Pipelife Inflex produced according to EN 61386-1 and -22
Certificate Intertek reference No: 1908359
VDE Zeichengenehmigung Certificate No: 40004853