


PVC SDR 13,6 BEND



PRODUKTBESKRIVELSE

PVC SDR 13,6 langbend brukes for maksimum driftstrykk 20 bar (PN 20) med en sikkerhetsfaktor på 2,0 – og 16 bar (PN 16) med en sikkerhetsfaktor på 2,5.

MÅLSKISSE



NRF-nr	D	α	z1	z2	r	Datablad
2361449	110 mm	11 °	463 mm	52 mm	385 mm	9010459219886
2361649	110 mm	22 °	427 mm	90 mm	385 mm	9010459219923
2361849	110 mm	30 °	402 mm	118 mm	385 mm	9010459219954
2362049	110 mm	45 °	457 mm	174 mm	385 mm	9010459219985
2362449	110 mm	90 °	680 mm	400 mm	387 mm	9010459220011
2361464	160 mm	11 °	631 mm	89 mm	560 mm	9010459219893
2361664	160 mm	22 °	579 mm	144 mm	560 mm	9010459219930
2361864	160 mm	30 °	542 mm	185 mm	560 mm	9010459219961
2362064	160 mm	45 °	697 mm	267 mm	560 mm	9010459219992
2362464	160 mm	90 °	955 mm	595 mm	560 mm	9010459220028
2361479	225 mm	11 °	835 mm	186 mm	788 mm	9010459219909
2361679	225 mm	22 °	761 mm	263 mm	788 mm	9010459219947
2361879	225 mm	30 °	709 mm	321 mm	788 mm	9010459219978
2362079	225 mm	45 °	818 mm	436 mm	788 mm	9010459220004
2362479	225 mm	90 °	1260 mm	898 mm	788 mm	9010459220035

PIPELIFE NORGE AS

6650 Surnadal / Norge

Telefon: +47 71 65 88 00 · Org.nr. 980 457 575

E-post: firmapost@pipelife.com