

PRAGMA® 45° GRENRØR SN 8




PRODUKTBESKRIVELSE

Rødbrune Pragma grenrør

Leveres med muffer i innløpene og med en spissende med tetningsring i utløpet.

MÅLSKISSE



NRF-nr	D	D1	α	z1	z2	z3	l1	l2	l3
3080353	160 mm	110 mm	45 °	108 mm	184 mm	183 mm	110 mm	97 mm	73 mm
3080355	160 mm	160 mm	45 °	133 mm	214 mm	214 mm	100 mm	97 mm	97 mm
3080357	200 mm	110 mm	45 °	99 mm	208 mm	208 mm	121 mm	116 mm	73 mm
3080359	200 mm	160 mm	45 °	134 mm	239 mm	239 mm	121 mm	116 mm	97 mm
3080362	200 mm	200 mm	45 °	153 mm	264 mm	264 mm	111 mm	116 mm	116 mm
3080371	250 mm	110 mm	45 °	155 mm	302 mm	240 mm	140 mm	134 mm	73 mm
3080374	250 mm	160 mm	45 °	155 mm	302 mm	270 mm	140 mm	134 mm	95 mm
3080377	250 mm	200 mm	45 °	155 mm	302 mm	300 mm	140 mm	134 mm	116 mm
3080378	250 mm	250 mm	45 °	155 mm	300 mm	296 mm	138 mm	131 mm	116 mm
3080381	315 mm	110 mm	45 °	139 mm	345 mm	290 mm	154 mm	146 mm	73 mm
3080384	315 mm	160 mm	45 °	139 mm	345 mm	320 mm	154 mm	146 mm	95 mm
3080387	315 mm	200 mm	45 °	139 mm	345 mm	338 mm	154 mm	146 mm	116 mm
3080391	315 mm	250 mm	45 °	213 mm	531 mm	360 mm	180 mm	148 mm	124 mm
3080392	315 mm	315 mm	45 °	249 mm	568 mm	539 mm	195 mm	173 mm	173 mm
3080394	400 mm	110 mm	45 °	96 mm	498 mm	419 mm	198 mm	158 mm	72 mm
3080401	400 mm	160 mm	45 °	131 mm	529 mm	458 mm	198 mm	158 mm	94 mm

PIPELIFE NORGE AS

6650 Surnadal / Norge

Telefon: +47 71 65 88 00 · Org.nr. 980 457 575

E-post: firmapost@pipelife.com

NRF-nr	D	D1	α	z1	z2	z3	l1	l2	l3
3080404	400 mm	200 mm	45 °	159 mm	567 mm	491 mm	198 mm	158 mm	113 mm
3080407	400 mm	250 mm	45 °	195 mm	598 mm	411 mm	198 mm	158 mm	124 mm
3080411	400 mm	315 mm	45 °	241 mm	651 mm	446 mm	198 mm	158 mm	130 mm
3080412	400 mm	400 mm	45 °	287 mm	705 mm	705 mm	213 mm	158 mm	158 mm
3080414	500 mm	110 mm	45 °	66 mm	611 mm	490 mm	212 mm	188 mm	72 mm
3080417	500 mm	160 mm	45 °	101 mm	618 mm	529 mm	212 mm	188 mm	94 mm
3080421	500 mm	200 mm	45 °	129 mm	675 mm	561 mm	212 mm	188 mm	113 mm
3080424	500 mm	250 mm	45 °	165 mm	682 mm	473 mm	212 mm	188 mm	124 mm
3080427	500 mm	315 mm	45 °	210 mm	764 mm	505 mm	212 mm	188 mm	130 mm
3080431	500 mm	400 mm	45 °	271 mm	831 mm	553 mm	212 mm	188 mm	141 mm
3080432	500 mm	500 mm	45 °	341 mm	807 mm	807 mm	232 mm	227 mm	227 mm
3080434	630 mm	110 mm	45 °	43 mm	699 mm	582 mm	248 mm	232 mm	72 mm
3080437	630 mm	160 mm	45 °	78 mm	763 mm	621 mm	248 mm	232 mm	94 mm
3080441	630 mm	200 mm	45 °	107 mm	784 mm	653 mm	248 mm	232 mm	113 mm
3080444	630 mm	250 mm	45 °	142 mm	848 mm	553 mm	248 mm	232 mm	124 mm
3080447	630 mm	315 mm	45 °	188 mm	902 mm	586 mm	248 mm	232 mm	130 mm
3080451	630 mm	400 mm	45 °	248 mm	941 mm	633 mm	248 mm	232 mm	141 mm
3080454	630 mm	500 mm	45 °	319 mm	969 mm	812 mm	248 mm	232 mm	179 mm
3080455	630 mm	630 mm	45 °	395 mm	1044 mm	992 mm	266 mm	280 mm	280 mm