

ISOTERM T600 RØR VANN



PRODUKTBESKRIVELSE

Medierør i PE100 SDR11 PN16.

Grått HDPE korrugert ytterrør.

Ohmsk brun varmekabel.

Anleggslengde pr. strømkurs: 300 – 600 m

[Gå til sammenstilling av dokumenter](#)

NRF-nr	d	e	D	l	Beskrivelse	Datablad
2405743	32 mm	3 mm	60 mm		Metervare	9010459155290
2405746	32 mm	3 mm	60 mm	200 m	Pall	9010459155269
2405749	32 mm	3 mm	60 mm	400 m	Pall	9010459155238
2405379	32 mm	3 mm	60 mm	800 m	K24 Trommel	9010459409423
2405756	40 mm	3,7 mm	70 mm		Metervare	9010459155177
2405759	40 mm	3,7 mm	70 mm	200 m	Pall	9010459155146
2405383	40 mm	3,7 mm	70 mm	600 m	K24 Trommel	9010459409454
2405766	50 mm	4,6 mm	90 mm		Metervare	9010459155085
2405769	50 mm	4,6 mm	90 mm	200 m	Kveil	9010459155054
2405773	63 mm	5,8 mm	125 mm		Metervare	9010459155023
2405776	63 mm	5,8 mm	125 mm	150 m	Kveil	9010459154996
2405779	75 mm	4,8 mm	125 mm		Metervare	9010459154965
2405783	75 mm	4,8 mm	125 mm	150 m	Kveil	9010459154934
2405786	90 mm	8,2 mm	175 mm		Metervare	9010459154903
2405789	90 mm	8,2 mm	175 mm	100 m	Kveil	9010459154873
2500003	110 mm	10 mm	175 mm		Metervare	9010459423399
2500009	110 mm	10 mm	175 mm	65 m	Kveil	9010459441263