

ISOTERM T600 RØR TRYKKAVLØP



PRODUKTBSKRIVELSE

Medierør i PE100 SDR11 PN16 .

Rødbrunt HDPE korrugert ytterrør.

Ohmsk brun varmekabel.

Anleggslengde pr. strømkurs: 300 – 600 m

[Gå til sammenstilling av dokumenter](#)

NRF-nr	d	e	D	l	Beskrivelse	Datablad
2405799	40 mm	3,7 mm	70 mm		Metervare	9010459154781
2405803	40 mm	3,7 mm	70 mm	200 m	Pall	9010459154750
2405386	40 mm	3,7 mm	70 mm	600 m	K24 Trommel	9010459409485
2405809	50 mm	4,6 mm	90 mm		Metervare	9010459154699
2405813	50 mm	4,6 mm	90 mm	200 m	Kveil	9010459154668
2405816	63 mm	5,8 mm	125 mm		Metervare	9010459154637
2405819	63 mm	5,8 mm	125 mm	150 m	Kveil	9010459154606
2405823	75 mm	6,8 mm	125 mm		Metervare	9010459154576
2405826	75 mm	6,8 mm	125 mm	150 m	150	9010459154545
2405829	90 mm	8,2 mm	175 mm		Metervare	9010459154514
2405833	90 mm	8,2 mm	175 mm	100 m	Kveil	9010459154484
2500006	110 mm	10 mm	175 mm		Metervare	9010459423429
2500013	110 mm	10 mm	175 mm	65 m	Kveil	9010459441294