

## ISOTERM T2000 RØR VANN



### PRODUKTBEKRIVELSE

Medierør i PE100 SDR11 PN16.  
Blått HDPE korrugert ytterør.  
Selvbegrensende varmekabel.

Dimensjon / Effekt / Anleggslengde pr. strømkurs:

20/45 mm / 7 W/m / 1 - 100 m

32/60 mm - 40/70 mm / 16 W/m / 1-110 m

50/90 mm - 63/125 mm / 25 W/m / 1-125 m

NRF-nr	d	e	D	l	Beskrivelse	Datablad
2405834	20 mm	2 mm	45 mm		Metervare	<a href="#">9010459154477</a>
2405835	20 mm	2 mm	45 mm	200 m	Kveil	<a href="#">9010459154460</a>
2405836	32 mm	3 mm	60 mm		Metervare	<a href="#">9010459154453</a>
2405837	32 mm	3 mm	60 mm	200 m	Pall	<a href="#">9010459154446</a>
2405387	32 mm	3 mm	60 mm	800 m	K24 Trommel	<a href="#">9010459409492</a>
2405839	40 mm	3,7 mm	70 mm		Metervare	<a href="#">9010459154422</a>
2405841	40 mm	3,7 mm	70 mm	200 m	Pall	<a href="#">9010459154415</a>
2405842	50 mm	4,6 mm	90 mm		Metervare	<a href="#">9010459154408</a>
2405843	50 mm	4,6 mm	90 mm	130 m	Kveil	<a href="#">9010459154392</a>
2405844	63 mm	5,8 mm	125 mm		Metervare	<a href="#">9010459154385</a>
2405845	63 mm	5,8 mm	125 mm	130 m	Kveil	<a href="#">9010459154378</a>