

STRAIGHT THROUGH BASE



PRODUCT DESCRIPTION

Chamber base have sockets type Eurosocket for connection with smooth-wall pipe or Pragma type for structural pipes Pragma. For Pragma pipe connection with socket type Eurosocket Pragma-PVC adaptor or Pragma Ecc Adaptor should be used. For smoothwall pipe connection with socket Pragma type stabilize click ring and sealing ring should be used.

SAP Index	SAP material description	Base type	Diameter	Outlet type	BUoM
3496101231	OS Base 630 0°/180° dim160	Pass-through	160 mm	Smooth pipe	EA
3496101232	OS Base 630 0°/180° dim200	Pass-through	200 mm	Smooth pipe	EA
3496102425	OS Base 630 0°/90°/0°/270° bend dim200	Pass-through	200 mm	Smooth pipe	EA
3496100638	Base ML 0°/90°or0°/270°dim250	Pass-through	250 mm	Pragma pipe	EA
3496101233	OS Base 630 0°/180° dim250	Pass-through	250 mm	Smooth pipe	EA
3496100648	Base ML 0°/135°or0°/225°dim250	Pass-through	250 mm	Pragma pipe	EA
3496100654	Base ML 0°/90°or0°/270°dim315	Pass-through	315 mm	Pragma pipe	EA
3496101234	OS Base 630 0°/180° dim315	Pass-through	315 mm	Smooth pipe	EA
3496100676	Base ML 0°/135°or0°/225°dim315	Pass-through	315 mm	Pragma pipe	EA
3496100771	Base ML 0°/180° dim400	Pass-through	400 mm	Pragma pipe	EA