

STRAIGHT THROUGH BASE



PRODUCT DESCRIPTION

Chamber base have sockets type Eurosocket for connection with smooth-wall pipe or Pragma type for structural pipes Pragma. For Pragma pipe connection with socket type Eurosocket Pragma-PVC adaptor or Pragma Ecc Adaptor should be used. For smoothwall pipe connection with socket Pragma type stabilize click ring and sealing ring should be used.

SAP Index	SAP material description	Base type	Diameter	Outlet type	BUoM
3496101306	OS Base 600 0°/180° dim160	Pass-through	160 mm	Smooth pipe	EA
3496101305	OS Base 600 0°/180° dim200	Pass-through	200 mm	Smooth pipe	EA
3496102404	OS Base 600 0°/90°/0°/270° bend dim200	Pass-through	200 mm	Smooth pipe	EA
3496101318	OS Base 600 0°/180° dim250	Pass-through	250 mm	Smooth pipe	EA
3496101307	OS Base 600 0°/180° dim315	Pass-through	315 mm	Smooth pipe	EA
3496101440	OS Base 600 0°/180° dim160 DIN Lock	Pass-through	160 mm	Smooth pipe	EA
3496101449	OS Base 600 0°/180° dim200 DIN Lock	Pass-through	200 mm	Smooth pipe	EA
3496102488	OS Base 600 0°/90°/0°/270° bend dim200 DIN Lock	Pass-through	200 mm	Smooth pipe	EA
3496101448	OS Base 600 0°/180° dim250 DIN Lock	Pass-through	250 mm	Smooth pipe	EA
3496101446	OS Base 600 0°/180° dim315 DIN Lock	Pass-through	315 mm	Smooth pipe	EA