

PVC PIPE, SN12 (SEWER LOCK)



PRODUCT DESCRIPTION

The Sewer-Lock connection guarantees leak-tightness over the entire service life, even with a deflection of the socket of 10% and the spigot end of 15% at up to 0.6 bar vacuum or up to 0.5 bar overpressure.

SAP Index	SAP material description	Diameter	Wall thickness	Length	Packing (pallet)	BUoM
3497102300	PVC Sewage Pipe 160/5.5/3 SN12 WK S-LOCK	160 mm	5,5 mm	3 m	28	EA
3497102302	PVC Sewage Pipe 160/5.5/6 SN12 WK S-LOCK	160 mm	5,5 mm	6 m	28	EA
3497102304	PVC Sewage Pipe 200/6.6/3 SN12 WK S-LOCK	200 mm	6,6 mm	3 m	25	EA
3497102306	PVC Sewage Pipe 200/6.6/6 SN12 WK S-LOCK	200 mm	6,6 mm	6 m	25	EA
3497102308	PVC Sewage Pipe 250/8.2/3 SN12 WK S-LOCK	250 mm	8,2 mm	3 m	16	EA
3497102309	PVC Sewage Pipe 250/8.2/6 SN12 WK S-LOCK	250 mm	8,2 mm	6 m	16	EA
3495201821	PVC Sewage Pipe 315/10.2/3 SN12 WK S-LOCK	315 mm	10,2 mm	3 m	6	EA
3495201822	PVC Sewage Pipe 315/10.2/6 SN12 WK S-LOCK	315 mm	10,2 mm	6 m	6	EA
3495201824	PVC Sewage Pipe 400/13.0/3 SN12 WK S-LOCK	400 mm	13,0 mm	3 m	3	EA
3495201825	PVC Sewage Pipe 400/13.0/6 SN12 WK S-LOCK	400 mm	13,0 mm	6 m	3	EA