

## PVC PIPE, SN8 (SEWER LOCK)



### PRODUCT DESCRIPTION

The Sewer-Lock connection guarantees leak-tightness over the entire service life, even with a deflection of the socket of 10% and the spigot end of 15% at up to 0.6 bar vacuum or up to 0.5 bar overpressure.

SAP Index	SAP material description	Diameter	Wall thickness	Length	Packing (pallet)	BUoM
3497100327	PVC Sewage Pipe 160/4.7/3 SN8 WK S-LOCK	160 mm	4,7 mm	3 m	28	EA
3497100422	PVC Sewage Pipe 160/4.7/6 SN8 WK S-LOCK	160 mm	4,7 mm	6 m	28	EA
3497100367	PVC Sewage Pipe 200/5.9/3 SN8 WK S-LOCK	200 mm	5,9 mm	3 m	25	EA
3497100438	PVC Sewage Pipe 200/5.9/6 SN8 WK S-LOCK	200 mm	5,9 mm	6 m	25	EA
3497100442	PVC Sewage Pipe 250/7.3/3 SN8 WK S-LOCK	250 mm	7,3 mm	3 m	16	EA
3497100496	PVC Sewage Pipe 250/7.3/6 SN8 WK S-LOCK	250 mm	7,3 mm	6 m	16	EA
3495200373	PVC Sewage Pipe 315/9.2/3 SN8 WK S-LOCK	315 mm	9,2 mm	3 m	6	EA
3495200369	PVC Sewage Pipe 315/9.2/6 SN8 WK S-LOCK	315 mm	9,2 mm	6 m	6	EA
3495200374	PVC Sewage Pipe 400/11.7/3 SN8 WK S-LOCK	400 mm	11,7 mm	3 m	3	EA
3495200370	PVC Sewage Pipe 400/11.7/6 SN8 WK S-LOCK	400 mm	11,7 mm	6 m	3	EA